

Hose capacity per series of reels

Max length of hose to be wound according to its outside diameter and spring rewinding power on hose reels supplied without hose (see below tables).

SERIES STANDARD AND INDUSTRIAL (OPEN AND ENCLOSED)

 Ø 12 mm	max 16 m	Series 270 inlet 3/8"
 Ø 14 mm	max 14 m	
 Ø 16 mm	max 10 m	

 Ø 12 mm	max 18 m	Series 300 inlet 3/8"-1/2"
 Ø 14 mm	max 16 m	
 Ø 16 mm	max 12 m	

 Ø 12 mm	max 22 m	Series 350 inlet 3/8"-1/2"
 Ø 14 mm	max 20 m	
 Ø 16 mm	max 18 m	

 Ø 17 mm	max 21 m	Series 440 Series 430 inlet 1/2"
 Ø 19,5 mm	max 16 m	
 Ø 22 mm	max 14 m	

 Ø 23 mm	max 20 m	Series 436 inlet 3/4"
 Ø 27 mm	max 15 m	

 Ø 23 mm	max 12 m	Series 437 inlet 3/4"
 Ø 27 mm	max 10 m	

 Ø 18,5 mm	max 28 m	Series 530 inlet 1/2"
 Ø 20 mm	max 26 m	
 Ø 22 mm	max 24 m	

 Ø 23 mm	max 20 m	Series 536 Series 537 inlet 3/4"
 Ø 27 mm	max 15 m	

 Ø 17 mm	max 30 m	Series 540 inlet 1/2"
 Ø 19,5 mm	max 30 m	
 Ø 22 mm	max 30 m	

 Ø 28 mm	max 22 m	Series 540 inlet 1"
 Ø 34 mm	max 17 m	

 Ø 17 mm	max 50 m	Series 560 inlet 1/2"
 Ø 19,5 mm	max 60 m	
 Ø 22 mm	max 60 m	

 Ø 30 mm	max 40 m	Series 560 inlet 1"
 Ø 35 mm	max 30 m	

SERIES INDUSTRIAL FOR OXYGEN-ACETYLENE TWIN HOSES

 Ø 13 +13 mm	max 13 m	Series 430 inlet 3/8"
 Ø 15 +15 mm	max 12 m	
 Ø 16 +16 mm	max 10 m	

 Ø 13 +13 mm	max 22 m	Series 530 inlet 3/8"
 Ø 15 +15 mm	max 20 m	
 Ø 16 +16 mm	max 15 m	

 Ø 13 +13 mm	max 37 m	Series 540 inlet 3/8"
 Ø 15 +15 mm	max 35 m	
 Ø 16 +16 mm	max 27 m	

SERIES INDUSTRIAL FOR LPG, METHANE

 Ø 15 mm	max 14 m	Series 300 inlet 3/8"
 Ø 17 mm	max 12 m	

 Ø 15 mm	max 18 m	Series 350 inlet 3/8"
 Ø 17 mm	max 17 m	

 Ø 15 mm	max 20 m	Series 430 inlet 3/8"
 Ø 17 mm	max 18 m	

 Ø 15 mm	max 28 m	Series 530 inlet 3/8"
 Ø 17 mm	max 27 m	

 Ø 15 mm	max 30 m	Series 540 inlet 3/8"
 Ø 17 mm	max 30 m	

SERIES INDUSTRIAL POWERED

 Ø 20 mm	max 50 m	Series 617 Series 618 inlet 1"
 Ø 27 mm	max 30 m	
 Ø 35 mm	max 20 m	

 Ø 27 mm	max 30 m	Series 617 inlet 1.1/2"
 Ø 35 mm	max 20 m	
 Ø 44 mm	max 15 m	
 Ø 50 mm	max 10 m	

 Ø 20 mm	max 100 m	Series 637 Series 638 inlet 1"
 Ø 27 mm	max 60 m	
 Ø 35 mm	max 40 m	

 Ø 27 mm	max 60 m	Series 637 inlet 1.1/2"
 Ø 35 mm	max 40 m	
 Ø 44 mm	max 30 m	
 Ø 50 mm	max 20 m	

Inlet connection hoses connecting hose reel to the system or to equipment

Inlet connection hoses connecting hose reel to the system or to equipment

Article	Length	Characteristic - Pressure	Inside - \varnothing - Outside	Inlet	Outlet	Connections
806/06	0,6 m	3/8" - hygienic - 400 bar	9,5 x 17,5	F 3/8"G	M 3/8"G	st. steel AISI 304
856/06	0,6 m	3/8" - hygienic - 200 bar	9,5 x 17	F 3/8"G	M 3/8"G	st. steel AISI 304
861/06	0,6 m	1/2" - hygienic - 10 bar	13 x 23	F 1/2"G	M 1/2"G	st. steel AISI 304
864/06	0,6 m	1/2" - hygienic - 100 bar	12,7 x 18,5	F 1/2"G	M 1/2"G	st. steel AISI 304
872/06	0,6 m	3/4" - rubber EPDM antistatic - 10 bar	19 x 27	F 3/4"G	M 1"G	st. steel AISI 316
881/06	0,6 m	1" - hygienic - 10 bar	25 x 37	F 1"G	M 1"G	st. steel AISI 304
884/06	0,6 m	1" - hygienic - 100 bar	25,4 x 31,5	F 1"G	M 1"G	st. steel AISI 304
906/06	0,6 m	3/8" - hygienic - 400 bar	9,5 x 17,5	F 3/8"G	M 3/8"G	zinc plated steel
907/06	0,6 m	3/8" - black rubber - 400 bar	9,5 x 17,5	F 3/8"G	M 3/8"G	zinc plated steel
911/2	1,5 m	8 x 12 - polyurethane - 20 bar	8 x 12	M 1/4"G	SNODO	brass
9113/06	0,6 m	1.1/2" - rubber NBR antistatic - 10 bar	38 x 50	F 1.1/2"G	M 1.1/2"G	zinc plated steel
921/2	1,5 m	10 x 14,5 - polyurethane - 20 bar	10 x 14,5	M 3/8"G	F 3/8"G	brass
952/06	0,6 m	3/8" - black rubber - 20 bar	9,5 x 16	F 3/8"G	M 3/8"G	zinc plated steel
955/06	0,6 m	3/8" - black rubber - 200 bar	9,5 x 17	F 3/8"G	M 3/8"G	zinc plated steel
956/06	0,6 m	3/8" - hygienic - 200 bar	9,5 x 17	F 3/8"G	M 3/8"G	zinc plated steel
957/06	0,6 m	3/8" - black rubber - 600 bar	9,5 x 18	F 3/8"G	M 3/8"G	zinc plated steel
959/2	1,5 m	3/8" - NBR-PVC - EN 559 - 20 bar	10 x 17	F 3/8"G-Sx	F 3/8"G-Sx	brass
960/06	0,6 m	1/2" - hygienic - 20 bar	12,7 x 20	F 1/2"G	M 1/2"G	zinc plated steel
961/2	1,5 m	13 x 19 - polyurethane - 20 bar	13 x 19	F 1/2"G	M 1/2"G	brass
963/06	0,6 m	1/2" - black rubber - 150 bar	12,7 x 19	F 1/2"G	M 1/2"G	zinc plated steel
964/06	0,6 m	1/2" - hygienic - 100 bar	12,7 x 20	F 1/2"G	M 1/2"G	zinc plated steel
967/06	0,6 m	1/2" - black rubber - 400 bar	12,7 x 21,5	F 1/2"G	M 1/2"G	zinc plated steel
968/06	0,6 m	1/2" - black rubber - 10 bar	13 x 20	F 1/2"G	M 1/2"G	zinc plated steel
980/06	0,6 m	1" - hygienic - 20 bar	25,4 x 33,5	F 1"G	M 1"G	zinc plated steel
983/06	0,6 m	1" - black rubber - 150 bar	25,4 x 31,5	F 1"G	M 1"G	zinc plated steel
984/06	0,6 m	1" - hygienic - 100 bar	25,4 x 33,5	F 1"G	M 1"G	zinc plated steel
988/06	0,6 m	1" - black rubber - 10 bar	25 x 35	F 1"G	M 1"G	zinc plated steel
995/2	1,5 m	2 x 3/8" - SBR-EPDM - EN 559 - 20 bar	9 + 9x16	F 3/8"G	F 3/8"G	brass



POLYURETHANE hoses



Air-Cold water 20 bar

Article	Length	Characteristic - Pressure	Inside - \varnothing - Outside	Inlet	Outlet	Connections
901/10	10 m	6 x 10 - polyurethane - 20 bar	6 x 10	M 3/8"G	M 1/4"G	brass
901/11	11 m	6 x 10 - polyurethane - 20 bar	6 x 10	M 1/4"G	M 1/4"G	brass
901/15	15 m	6 x 10 - polyurethane - 20 bar	6 x 10	M 3/8"G	M 1/4"G	brass
911/11	11 m	8 x 12 - polyurethane - 20 bar	8 x 12	M 1/4"G	M 1/4"G	brass
911/15	15 m	8 x 12 - polyurethane - 20 bar	8 x 12	M 3/8"G	M 1/4"G	brass
911/18	18 m	8 x 12 - polyurethane - 20 bar	8 x 12	M 3/8"G	M 1/4"G	brass
911/20	20 m	8 x 12 - polyurethane - 20 bar	8 x 12	M 3/8"G	M 1/4"G	brass
921/13	13 m	10 x 14,5 - polyurethane - 20 bar	10 x 14,5	M 3/8"G	M 3/8"G	brass
921/15	15 m	10 x 14,5 - polyurethane - 20 bar	10 x 14,5	M 3/8"G	M 3/8"G	brass
921/20	20 m	10 x 14,5 - polyurethane - 20 bar	10 x 14,5	M 3/8"G	M 3/8"G	brass
961/8	8 m	13 x 19 - polyurethane - 20 bar	13 x 19	M 3/8"G	M 1/2"G	brass
961/10	10 m	13 x 19 - polyurethane - 20 bar	13 x 19	M 3/8"G	M 1/2"G	brass
961/11	10 m	13 x 19 - polyurethane - 20 bar	13 x 19	F 1/2"G	M 1/2"G	brass
961/12	12 m	13 x 19 - polyurethane - 20 bar	13 x 19	M 3/8"G	M 1/2"G	brass
961/14	15 m	13 x 19 - polyurethane - 20 bar	13 x 19	M 3/8"G	M 1/2"G	brass
961/15	15 m	13 x 19 - polyurethane - 20 bar	13 x 19	F 1/2"G	M 1/2"G	brass



Air-Cold water 20 bar

Article	Length	Characteristic - Pressure	Inside - \varnothing - Outside	Inlet	Outlet	Connections
952/10	10 m	3/8" - black rubber - 20 bar	9,5 x 16	M 3/8"G	M 3/8"G	zinc plated steel
952/12	12 m	3/8" - black rubber - 20 bar	9,5 x 16	M 3/8"G	M 3/8"G	zinc plated steel
952/13	12 m	3/8" - black rubber - 20 bar	9,5 x 16	F 3/8"G	M 3/8"G	zinc plated steel
952/18	18 m	3/8" - black rubber - 20 bar	9,5 x 16	M 3/8"G	M 3/8"G	zinc plated steel
952/19	18 m	3/8" - black rubber - 20 bar	9,5 x 16	F 3/8"G	M 3/8"G	zinc plated steel
962/10	10 m	1/2" - black rubber - 20 bar	12,7 x 20	F 1/2"G	M 1/2"G	zinc plated steel
962/15	15 m	1/2" - black rubber - 20 bar	12,7 x 20	F 1/2"G	M 1/2"G	zinc plated steel
962/20	20 m	1/2" - black rubber - 20 bar	12,7 x 20	F 1/2"G	M 1/2"G	zinc plated steel
962/25	25 m	1/2" - black rubber - 20 bar	12,7 x 20	F 1/2"G	M 1/2"G	zinc plated steel
962/30	30 m	1/2" - black rubber - 20 bar	12,7 x 20	F 1/2"G	M 1/2"G	zinc plated steel
962/40	40 m	1/2" - black rubber - 20 bar	12,7 x 20	F 1/2"G	M 1/2"G	zinc plated steel
962/50	50 m	1/2" - black rubber - 20 bar	12,7 x 20	F 1/2"G	M 1/2"G	zinc plated steel
962/60	60 m	1/2" - black rubber - 20 bar	12,7 x 20	F 1/2"G	M 1/2"G	zinc plated steel
962/70	70 m	1/2" - black rubber - 20 bar	12,7 x 20	F 1/2"G	M 1/2"G	zinc plated steel
962/80	80 m	1/2" - black rubber - 20 bar	12,7 x 20	F 1/2"G	M 1/2"G	zinc plated steel
962/90	90 m	1/2" - black rubber - 20 bar	12,7 x 20	F 1/2"G	M 1/2"G	zinc plated steel
962/100	100 m	1/2" - black rubber - 20 bar	12,7 x 20	F 1/2"G	M 1/2"G	zinc plated steel
972/15	15 m	3/4" - black rubber - 20 bar	19 x 26,5	F 3/4"G	M 3/4"G	zinc plated steel
972/20	20 m	3/4" - black rubber - 20 bar	19 x 26,5	F 3/4"G	M 3/4"G	zinc plated steel
972/30	30 m	3/4" - black rubber - 20 bar	19 x 26,5	F 3/4"G	M 3/4"G	zinc plated steel
972/35	35 m	3/4" - black rubber - 20 bar	19 x 26,5	F 3/4"G	M 3/4"G	zinc plated steel
972/40	40 m	3/4" - black rubber - 20 bar	19 x 26,5	F 3/4"G	M 3/4"G	zinc plated steel
972/50	50 m	3/4" - black rubber - 20 bar	19 x 26,5	F 3/4"G	M 3/4"G	zinc plated steel
972/60	60 m	3/4" - black rubber - 20 bar	19 x 26,5	F 3/4"G	M 3/4"G	zinc plated steel
982/15	15 m	1" - black rubber - 20 bar	25,4 x 32,5	F 1"G	M 1"G	zinc plated steel
982/20	20 m	1" - black rubber - 20 bar	25,4 x 32,5	F 1"G	M 1"G	zinc plated steel
982/30	30 m	1" - black rubber - 20 bar	25,4 x 32,5	F 1"G	M 1"G	zinc plated steel
982/40	40 m	1" - black rubber - 20 bar	25,4 x 32,5	F 1"G	M 1"G	zinc plated steel

BLACK SYNTHETIC RUBBER hoses



Water-Hot water 130°C 100 bar

Article	Length	Characteristic - Pressure	Inside - \varnothing - Outside	Inlet	Outlet	Connections
953/13	12 m	3/8" - black rubber - 100 bar	9,5 x 15	M 3/8"G	M 3/8"G	zinc plated steel
953/18	17 m	3/8" - black rubber - 100 bar	9,5 x 15	M 3/8"G	M 3/8"G	zinc plated steel
963/7	8 m	1/2" - black rubber - 100 bar	12,7 x 18,5	M 1/2"G	M 1/2"G	zinc plated steel
963/9	10 m	1/2" - black rubber - 100 bar	12,7 x 18,5	M 1/2"G	M 1/2"G	zinc plated steel
963/12	10 m	1/2" - black rubber - 100 bar	12,7 x 18,5	F 1/2"G	M 1/2"G	zinc plated steel
963/14	15 m	1/2" - black rubber - 100 bar	12,7 x 18,5	F 1/2"G	M 1/2"G	zinc plated steel
963/19	20 m	1/2" - black rubber - 100 bar	12,7 x 18,5	F 1/2"G	M 1/2"G	zinc plated steel
963/24	25 m	1/2" - black rubber - 100 bar	12,7 x 18,5	F 1/2"G	M 1/2"G	zinc plated steel
963/29	30 m	1/2" - black rubber - 100 bar	12,7 x 18,5	F 1/2"G	M 1/2"G	zinc plated steel
963/39	40 m	1/2" - black rubber - 100 bar	12,7 x 18,5	F 1/2"G	M 1/2"G	zinc plated steel
963/49	50 m	1/2" - black rubber - 100 bar	12,7 x 18,5	F 1/2"G	M 1/2"G	zinc plated steel
963/59	60 m	1/2" - black rubber - 100 bar	12,7 x 18,5	F 1/2"G	M 1/2"G	zinc plated steel
963/69	70 m	1/2" - black rubber - 100 bar	12,7 x 18,5	F 1/2"G	M 1/2"G	zinc plated steel
963/79	80 m	1/2" - black rubber - 100 bar	12,7 x 18,5	F 1/2"G	M 1/2"G	zinc plated steel
963/89	90 m	1/2" - black rubber - 100 bar	12,7 x 18,5	F 1/2"G	M 1/2"G	zinc plated steel
963/99	100 m	1/2" - black rubber - 100 bar	12,7 x 18,5	F 1/2"G	M 1/2"G	zinc plated steel
973/14	15 m	3/4" - black rubber - 100 bar	19 x 25	F 3/4"G	M 3/4"G	zinc plated steel
973/19	20 m	3/4" - black rubber - 100 bar	19 x 25	F 3/4"G	M 3/4"G	zinc plated steel
973/29	30 m	3/4" - black rubber - 100 bar	19 x 25	F 3/4"G	M 3/4"G	zinc plated steel
973/34	35 m	3/4" - black rubber - 100 bar	19 x 25	F 3/4"G	M 3/4"G	zinc plated steel
973/39	40 m	3/4" - black rubber - 100 bar	19 x 25	F 3/4"G	M 3/4"G	zinc plated steel
973/49	50 m	3/4" - black rubber - 100 bar	19 x 25	F 3/4"G	M 3/4"G	zinc plated steel
973/59	60 m	3/4" - black rubber - 100 bar	19 x 25	F 3/4"G	M 3/4"G	zinc plated steel
983/15	15 m	1" - black rubber - 100 bar	25,4 x 31,5	F 1"G	M 1"G	zinc plated steel
983/19	20 m	1" - black rubber - 100 bar	25,4 x 31,5	F 1"G	M 1"G	zinc plated steel
983/29	30 m	1" - black rubber - 100 bar	25,4 x 31,5	F 1"G	M 1"G	zinc plated steel
983/39	40 m	1" - black rubber - 100 bar	25,4 x 31,5	F 1"G	M 1"G	zinc plated steel

Water-Hot water 130°C 200 bar

Article	Length	Characteristic - Pressure	Inside - \varnothing - Outside	Inlet	Outlet	Connections
943/12	12 m	5/16" - black rubber - 200 bar	8 x 15	M 3/8"G	F 3/8"G	zinc plated steel
943/17	17 m	5/16" - black rubber - 200 bar	8 x 15	M 3/8"G	F 3/8"G	zinc plated steel
955/12	12 m	3/8" - black rubber - 200 bar	9,5 x 17	F 3/8"G	F 3/8"G	zinc plated steel
955/18	18 m	3/8" - black rubber - 200 bar	9,5 x 17	F 3/8"G	F 3/8"G	zinc plated steel
955/20	20 m	3/8" - black rubber - 200 bar	9,5 x 17	F 3/8"G	F 3/8"G	zinc plated steel
955/25	25 m	3/8" - black rubber - 200 bar	9,5 x 17	F 3/8"G	F 3/8"G	zinc plated steel
955/30	30 m	3/8" - black rubber - 200 bar	9,5 x 17	F 3/8"G	F 3/8"G	zinc plated steel
955/40	40 m	3/8" - black rubber - 200 bar	9,5 x 17	F 3/8"G	F 3/8"G	zinc plated steel
955/50	50 m	3/8" - black rubber - 200 bar	9,5 x 17	F 3/8"G	F 3/8"G	zinc plated steel

Water-Hot water 130°C 400 bar

Article	Length	Characteristic - Pressure	Inside - \varnothing - Outside	Inlet	Outlet	Connections
945/12	12 m	5/16" - black rubber - 400 bar	8 x 16	M 3/8"G	F 3/8"G	zinc plated steel
945/17	17 m	5/16" - black rubber - 400 bar	8 x 16	M 3/8"G	F 3/8"G	zinc plated steel
907/12	12 m	3/8" - black rubber - 400 bar	9,5 x 17,5	F 3/8"G	F 3/8"G	zinc plated steel
907/18	18 m	3/8" - black rubber - 400 bar	9,5 x 17,5	F 3/8"G	F 3/8"G	zinc plated steel
907/20	20 m	3/8" - black rubber - 400 bar	9,5 x 17,5	F 3/8"G	F 3/8"G	zinc plated steel
907/25	25 m	3/8" - black rubber - 400 bar	9,5 x 17,5	F 3/8"G	F 3/8"G	zinc plated steel
907/30	30 m	3/8" - black rubber - 400 bar	9,5 x 17,5	F 3/8"G	F 3/8"G	zinc plated steel
907/40	40 m	3/8" - black rubber - 400 bar	9,5 x 17,5	F 3/8"G	F 3/8"G	zinc plated steel
907/50	50 m	3/8" - black rubber - 400 bar	9,5 x 17,5	F 3/8"G	F 3/8"G	zinc plated steel



Blue hygienic synthetic rubber hoses

Blue hygienic air-cold water 20 bar

Article	Length	Characteristic - Pressure	Inside - \emptyset - Outside	Inlet	Outlet	Connections
950/12	12 m	3/8" - hygienic - 20 bar	9,5 x 17	M 3/8"G	M 3/8"G	zinc plated steel
950/17	17 m	3/8" - hygienic - 20 bar	9,5 x 17	M 3/8"G	M 3/8"G	zinc plated steel
960/10	10 m	1/2" - hygienic - 20 bar	12,7 x 20	F 1/2"G	M 1/2"G	zinc plated steel
960/15	15 m	1/2" - hygienic - 20 bar	12,7 x 20	F 1/2"G	M 1/2"G	zinc plated steel
960/20	20 m	1/2" - hygienic - 20 bar	12,7 x 20	F 1/2"G	M 1/2"G	zinc plated steel
960/25	25 m	1/2" - hygienic - 20 bar	12,7 x 20	F 1/2"G	M 1/2"G	zinc plated steel
960/30	30 m	1/2" - hygienic - 20 bar	12,7 x 20	F 1/2"G	M 1/2"G	zinc plated steel
960/40	40 m	1/2" - hygienic - 20 bar	12,7 x 20	F 1/2"G	M 1/2"G	zinc plated steel
960/50	50 m	1/2" - hygienic - 20 bar	12,7 x 20	F 1/2"G	M 1/2"G	zinc plated steel
960/60	60 m	1/2" - hygienic - 20 bar	12,7 x 20	F 1/2"G	M 1/2"G	zinc plated steel
970/15	15 m	3/4" - hygienic - 20 bar	19 x 26	F 3/4"G	M 3/4"G	zinc plated steel
970/20	20 m	3/4" - hygienic - 20 bar	19 x 26	F 3/4"G	M 3/4"G	zinc plated steel
970/30	30 m	3/4" - hygienic - 20 bar	19 x 26	F 3/4"G	M 3/4"G	zinc plated steel
970/35	35 m	3/4" - hygienic - 20 bar	19 x 26	F 3/4"G	M 3/4"G	zinc plated steel
970/40	40 m	3/4" - hygienic - 20 bar	19 x 26	F 3/4"G	M 3/4"G	zinc plated steel
980/15	15 m	1" - hygienic - 20 bar	25,4 x 33,5	F 1"G	M 1"G	zinc plated steel
980/20	20 m	1" - hygienic - 20 bar	25,4 x 33,5	F 1"G	M 1"G	zinc plated steel
980/30	30 m	1" - hygienic - 20 bar	25,4 x 33,5	F 1"G	M 1"G	zinc plated steel

Blue hygienic water-hot water 130°C 100 bar

Article	Length	Characteristic - Pressure	Inside - \emptyset - Outside	Inlet	Outlet	Connections
954/13	12 m	3/8" - hygienic - 100 bar	9,5 x 17	M 3/8"G	M 3/8"G	zinc plated steel
954/18	17 m	3/8" - hygienic - 100 bar	9,5 x 17	M 3/8"G	M 3/8"G	zinc plated steel
964/8	8 m	1/2" - hygienic - 100 bar	12,7 x 20	M 1/2"G	M 1/2"G	zinc plated steel
964/10	10 m	1/2" - hygienic - 100 bar	12,7 x 20	M 1/2"G	M 1/2"G	zinc plated steel
964/11	10 m	1/2" - hygienic - 100 bar	12,7 x 20	F 1/2"G	M 1/2"G	zinc plated steel
964/15	15 m	1/2" - hygienic - 100 bar	12,7 x 20	F 1/2"G	M 1/2"G	zinc plated steel
964/20	20 m	1/2" - hygienic - 100 bar	12,7 x 20	F 1/2"G	M 1/2"G	zinc plated steel
964/25	25 m	1/2" - hygienic - 100 bar	12,7 x 20	F 1/2"G	M 1/2"G	zinc plated steel
964/30	30 m	1/2" - hygienic - 100 bar	12,7 x 20	F 1/2"G	M 1/2"G	zinc plated steel
964/40	40 m	1/2" - hygienic - 100 bar	12,7 x 20	F 1/2"G	M 1/2"G	zinc plated steel
964/50	50 m	1/2" - hygienic - 100 bar	12,7 x 20	F 1/2"G	M 1/2"G	zinc plated steel
964/60	60 m	1/2" - hygienic - 100 bar	12,7 x 20	F 1/2"G	M 1/2"G	zinc plated steel
974/15	15 m	3/4" - hygienic - 100 bar	19 x 26	F 3/4"G	M 3/4"G	zinc plated steel
974/20	20 m	3/4" - hygienic - 100 bar	19 x 26	F 3/4"G	M 3/4"G	zinc plated steel
974/30	30 m	3/4" - hygienic - 100 bar	19 x 26	F 3/4"G	M 3/4"G	zinc plated steel
974/35	35 m	3/4" - hygienic - 100 bar	19 x 26	F 3/4"G	M 3/4"G	zinc plated steel
974/40	40m	3/4" - hygienic - 100 bar	19 x 26	F 3/4"G	M 3/4"G	zinc plated steel
984/14	15 m	1" - hygienic - 100 bar	25,4 x 33,5	F 1"G	M 1"G	zinc plated steel
984/20	20 m	1" - hygienic - 100 bar	25,4 x 33,5	F 1"G	M 1"G	zinc plated steel
984/30	30 m	1" - hygienic - 100 bar	25,4 x 33,5	F 1"G	M 1"G	zinc plated steel

SYNTHETIC RUBBER hoses



Blue hygienic water-hot water 130°C 200 bar

Article	Length	Characteristic - Pressure	Inside - \varnothing - Outside	Inlet	Outlet	Connections
944/12	12 m	5/16" - hygienic - 200 bar	8 x 15	M 3/8"G	F 3/8"G	zinc plated steel
944/17	17 m	5/16" - hygienic - 200 bar	8 x 15	M 3/8"G	F 3/8"G	zinc plated steel
956/12	12 m	3/8" - hygienic - 200 bar	9,5 x 17	F 3/8"G	F 3/8"G	zinc plated steel
956/18	18 m	3/8" - hygienic - 200 bar	9,5 x 17	F 3/8"G	F 3/8"G	zinc plated steel
956/20	20 m	3/8" - hygienic - 200 bar	9,5 x 17	F 3/8"G	F 3/8"G	zinc plated steel
956/25	25 m	3/8" - hygienic - 200 bar	9,5 x 17	F 3/8"G	F 3/8"G	zinc plated steel
956/30	30 m	3/8" - hygienic - 200 bar	9,5 x 17	F 3/8"G	F 3/8"G	zinc plated steel
956/40	40 m	3/8" - hygienic - 200 bar	9,5 x 17	F 3/8"G	F 3/8"G	zinc plated steel
956/50	50 m	3/8" - hygienic - 200 bar	9,5 x 17	F 3/8"G	F 3/8"G	zinc plated steel

Blue hygienic water-hot water 130°C 400 bar

Article	Length	Characteristic - Pressure	Inside - \varnothing - Outside	Inlet	Outlet	Connections
946/12	12 m	5/16" - hygienic - 400 bar	8 x 16	M 3/8"G	F 3/8"G	zinc plated steel
946/17	17 m	5/16" - hygienic - 400 bar	8 x 16	M 3/8"G	F 3/8"G	zinc plated steel
906/12	12 m	3/8" - hygienic - 400 bar	9,5 x 17,5	F 3/8"G	F 3/8"G	zinc plated steel
906/18	18 m	3/8" - hygienic - 400 bar	9,5 x 17,5	F 3/8"G	F 3/8"G	zinc plated steel
906/20	20 m	3/8" - hygienic - 400 bar	9,5 x 17,5	F 3/8"G	F 3/8"G	zinc plated steel
906/25	25 m	3/8" - hygienic - 400 bar	9,5 x 17,5	F 3/8"G	F 3/8"G	zinc plated steel
906/30	30 m	3/8" - hygienic - 400 bar	9,5 x 17,5	F 3/8"G	F 3/8"G	zinc plated steel
906/40	40 m	3/8" - hygienic - 400 bar	9,5 x 17,5	F 3/8"G	F 3/8"G	zinc plated steel
906/50	50 m	3/8" - hygienic - 400 bar	9,5 x 17,5	F 3/8"G	F 3/8"G	zinc plated steel

Blue hygienic synthetic rubber hoses with stainless steel AISI 304 connections

Blue atoxic hygienic for air-cold water 10 bar

Article	Length	Characteristic - Pressure	Inside - \varnothing - Outside	Inlet	Outlet	Connections
861/10	10 m	1/2" - hygienic - 10 bar	13 x 23	F 1/2"G	M 1/2"G	st. steel AISI 304
861/15	15 m	1/2" - hygienic - 10 bar	13 x 23	F 1/2"G	M 1/2"G	st. steel AISI 304
861/20	20 m	1/2" - hygienic - 10 bar	13 x 23	F 1/2"G	M 1/2"G	st. steel AISI 304
861/25	25 m	1/2" - hygienic - 10 bar	13 x 23	F 1/2"G	M 1/2"G	st. steel AISI 304
861/30	30 m	1/2" - hygienic - 10 bar	13 x 23	F 1/2"G	M 1/2"G	st. steel AISI 304
861/40	40 m	1/2" - hygienic - 10 bar	13 x 23	F 1/2"G	M 1/2"G	st. steel AISI 304
861/50	50 m	1/2" - hygienic - 10 bar	13 x 23	F 1/2"G	M 1/2"G	st. steel AISI 304
861/60	60 m	1/2" - hygienic - 10 bar	13 x 23	F 1/2"G	M 1/2"G	st. steel AISI 304
871/15	15 m	3/4" - hygienic - 10 bar	19 x 30	F 3/4"G	M 3/4"G	st. steel AISI 304
871/20	20 m	3/4" - hygienic - 10 bar	19 x 30	F 3/4"G	M 3/4"G	st. steel AISI 304
871/30	30 m	3/4" - hygienic - 10 bar	19 x 30	F 3/4"G	M 3/4"G	st. steel AISI 304
871/35	35 m	3/4" - hygienic - 10 bar	19 x 30	F 3/4"G	M 3/4"G	st. steel AISI 304
871/40	40 m	3/4" - hygienic - 10 bar	19 x 30	F 3/4"G	M 3/4"G	st. steel AISI 304
881/15	15 m	1" - hygienic - 10 bar	25 x 37	F 1"G	M 1"G	st. steel AISI 304
881/20	20 m	1" - hygienic - 10 bar	25 x 37	F 1"G	M 1"G	st. steel AISI 304
881/30	30 m	1" - hygienic - 10 bar	25 x 37	F 1"G	M 1"G	st. steel AISI 304



Blue hygienic synthetic rubber hoses with stainless steel AISI 304 couplings

Blue hygienic for water-hot water 130°C 100 bar

Article	Length	Characteristic - Pressure	Inside - \emptyset - Outside	Inlet	Outlet	Connections
864/10	10 m	1/2" - hygienic - 100 bar	12,7 x 18,5	F 1/2"G	M 1/2"G	st. steel AISI 304
864/15	15 m	1/2" - hygienic - 100 bar	12,7 x 18,5	F 1/2"G	M 1/2"G	st. steel AISI 304
864/20	20 m	1/2" - hygienic - 100 bar	12,7 x 18,5	F 1/2"G	M 1/2"G	st. steel AISI 304
864/25	25 m	1/2" - hygienic - 100 bar	12,7 x 18,5	F 1/2"G	M 1/2"G	st. steel AISI 304
864/30	30 m	1/2" - hygienic - 100 bar	12,7 x 18,5	F 1/2"G	M 1/2"G	st. steel AISI 304
864/40	40 m	1/2" - hygienic - 100 bar	12,7 x 18,5	F 1/2"G	M 1/2"G	st. steel AISI 304
864/50	50 m	1/2" - hygienic - 100 bar	12,7 x 18,5	F 1/2"G	M 1/2"G	st. steel AISI 304
864/60	60 m	1/2" - hygienic - 100 bar	12,7 x 18,5	F 1/2"G	M 1/2"G	st. steel AISI 304
874/15	15 m	3/4" - hygienic - 100 bar	19 x 25	F 3/4"G	M 3/4"G	st. steel AISI 304
874/20	20 m	3/4" - hygienic - 100 bar	19 x 25	F 3/4"G	M 3/4"G	st. steel AISI 304
874/30	30 m	3/4" - hygienic - 100 bar	19 x 25	F 3/4"G	M 3/4"G	st. steel AISI 304
874/35	35 m	3/4" - hygienic - 100 bar	19 x 25	F 3/4"G	M 3/4"G	st. steel AISI 304
874/40	40 m	3/4" - hygienic - 100 bar	19 x 25	F 3/4"G	M 3/4"G	st. steel AISI 304
884/14	15 m	1" - hygienic - 100 bar	25,4 x 31,5	F 1"G	M 1"G	st. steel AISI 304
884/20	20 m	1" - hygienic - 100 bar	25,4 x 31,5	F 1"G	M 1"G	st. steel AISI 304
884/30	30 m	1" - hygienic - 100 bar	25,4 x 31,5	F 1"G	M 1"G	st. steel AISI 304

Blue hygienic for water-hot water 130°C 200 bar

Article	Length	Characteristic - Pressure	Inside - \emptyset - Outside	Inlet	Outlet	Connections
856/12	12 m	3/8" - hygienic - 200 bar	9,5 x 17	F 3/8"G	F 3/8"G	st. steel AISI 304
856/18	18 m	3/8" - hygienic - 200 bar	9,5 x 17	F 3/8"G	F 3/8"G	st. steel AISI 304
856/20	20 m	3/8" - hygienic - 200 bar	9,5 x 17	F 3/8"G	F 3/8"G	st. steel AISI 304
856/25	25 m	3/8" - hygienic - 200 bar	9,5 x 17	F 3/8"G	F 3/8"G	st. steel AISI 304
856/30	30 m	3/8" - hygienic - 200 bar	9,5 x 17	F 3/8"G	F 3/8"G	st. steel AISI 304
856/40	40 m	3/8" - hygienic - 200 bar	9,5 x 17	F 3/8"G	F 3/8"G	st. steel AISI 304
856/50	50 m	3/8" - hygienic - 200 bar	9,5 x 17	F 3/8"G	F 3/8"G	st. steel AISI 304

Blue hygienic for water-hot water 130°C 400 bar

Article	Length	Characteristic - Pressure	Inside - \emptyset - Outside	Inlet	Outlet	Connections
806/12	12 m	3/8" - hygienic - 400 bar	9,5 x 17,5	F 3/8"G	F 3/8"G	st. steel AISI 304
806/18	18 m	3/8" - hygienic - 400 bar	9,5 x 17,5	F 3/8"G	F 3/8"G	st. steel AISI 304
806/20	20 m	3/8" - hygienic - 400 bar	9,5 x 17,5	F 3/8"G	F 3/8"G	st. steel AISI 304
806/25	25 m	3/8" - hygienic - 400 bar	9,5 x 17,5	F 3/8"G	F 3/8"G	st. steel AISI 304
806/30	30 m	3/8" - hygienic - 400 bar	9,5 x 17,5	F 3/8"G	F 3/8"G	st. steel AISI 304
806/40	40 m	3/8" - hygienic - 400 bar	9,5 x 17,5	F 3/8"G	F 3/8"G	st. steel AISI 304
806/50	50 m	3/8" - hygienic - 400 bar	9,5 x 17,5	F 3/8"G	F 3/8"G	st. steel AISI 304

LUBRICATION hoses



Lubrication hoses (oil, antifreeze, grease and allied products)

Oil, antifreeze and allied products 150 bar

Article	Length	Characteristic - Pressure	Inside - \varnothing - Outside	Inlet	Outlet	Connections
953/12	12 m	3/8" - black rubber - 150 bar	9,5 x 17	M 3/8"G	M 1/2"G	zinc plated steel
953/17	17 m	3/8" - black rubber - 150 bar	9,5 x 17	M 3/8"G	M 1/2"G	zinc plated steel
963/8	8 m	1/2" - black rubber - 150 bar	12,7 x 19	M 1/2"G	M 1/2"G	zinc plated steel
963/10	10 m	1/2" - black rubber - 150 bar	12,7 x 19	M 1/2"G	M 1/2"G	zinc plated steel
963/11	10 m	1/2" - black rubber - 150 bar	12,7 x 19	F 1/2"G	M 1/2"G	zinc plated steel
963/15	15 m	1/2" - black rubber - 150 bar	12,7 x 19	F 1/2"G	M 1/2"G	zinc plated steel
963/20	20 m	1/2" - black rubber - 150 bar	12,7 x 19	F 1/2"G	M 1/2"G	zinc plated steel
963/25	25 m	1/2" - black rubber - 150 bar	12,7 x 19	F 1/2"G	M 1/2"G	zinc plated steel
963/30	30 m	1/2" - black rubber - 150 bar	12,7 x 19	F 1/2"G	M 1/2"G	zinc plated steel
963/40	40 m	1/2" - black rubber - 150 bar	12,7 x 19	F 1/2"G	M 1/2"G	zinc plated steel
963/50	50 m	1/2" - black rubber - 150 bar	12,7 x 19	F 1/2"G	M 1/2"G	zinc plated steel
963/60	60 m	1/2" - black rubber - 150 bar	12,7 x 19	F 1/2"G	M 1/2"G	zinc plated steel
963/70	70 m	1/2" - black rubber - 150 bar	12,7 x 19	F 1/2"G	M 1/2"G	zinc plated steel
963/80	80 m	1/2" - black rubber - 150 bar	12,7 x 19	F 1/2"G	M 1/2"G	zinc plated steel
963/90	90 m	1/2" - black rubber - 150 bar	12,7 x 19	F 1/2"G	M 1/2"G	zinc plated steel
963/100	100 m	1/2" - black rubber - 150 bar	12,7 x 19	F 1/2"G	M 1/2"G	zinc plated steel
973/15	15 m	3/4" - black rubber - 150 bar	19 x 26,5	F 3/4"G	M 3/4"G	zinc plated steel
973/20	20 m	3/4" - black rubber - 150 bar	19 x 26,5	F 3/4"G	M 3/4"G	zinc plated steel
973/30	30 m	3/4" - black rubber - 150 bar	19 x 26,5	F 3/4"G	M 3/4"G	zinc plated steel
973/35	35 m	3/4" - black rubber - 150 bar	19 x 26,5	F 3/4"G	M 3/4"G	zinc plated steel
973/40	40 m	3/4" - black rubber - 150 bar	19 x 26,5	F 3/4"G	M 3/4"G	zinc plated steel
973/50	50 m	3/4" - black rubber - 150 bar	19 x 26,5	F 3/4"G	M 3/4"G	zinc plated steel
973/60	60 m	3/4" - black rubber - 150 bar	19 x 26,5	F 3/4"G	M 3/4"G	zinc plated steel
983/14	15 m	1" - black rubber - 150 bar	25,4 x 35,5	F 1"G	M 1"G	zinc plated steel
983/20	20 m	1" - black rubber - 150 bar	25,4 x 35,5	F 1"G	M 1"G	zinc plated steel
983/30	30 m	1" - black rubber - 150 bar	25,4 x 35,5	F 1"G	M 1"G	zinc plated steel
983/40	40 m	1" - black rubber - 150 bar	25,4 x 35,5	F 1"G	M 1"G	zinc plated steel

Grease 400 bar

Article	Length	Characteristic - Pressure	Inside - \varnothing - Outside	Inlet	Outlet	Connections
967/30	30 m	1/2" - black rubber - 400 bar	12,7 x 21,5	F 1/2"G	M 1/2"G	zinc plated steel
967/40	40 m	1/2" - black rubber - 400 bar	12,7 x 21,5	F 1/2"G	M 1/2"G	zinc plated steel
967/50	50 m	1/2" - black rubber - 400 bar	12,7 x 21,5	F 1/2"G	M 1/2"G	zinc plated steel
967/60	60 m	1/2" - black rubber - 400 bar	12,7 x 21,5	F 1/2"G	M 1/2"G	zinc plated steel
967/70	70 m	1/2" - black rubber - 400 bar	12,7 x 21,5	F 1/2"G	M 1/2"G	zinc plated steel
967/80	80 m	1/2" - black rubber - 400 bar	12,7 x 21,5	F 1/2"G	M 1/2"G	zinc plated steel
967/90	90 m	1/2" - black rubber - 400 bar	12,7 x 21,5	F 1/2"G	M 1/2"G	zinc plated steel
967/100	100 m	1/2" - black rubber - 400 bar	12,7 x 21,5	F 1/2"G	M 1/2"G	zinc plated steel

Grease 600 bar

Article	Length	Characteristic - Pressure	Inside - \varnothing - Outside	Inlet	Outlet	Connections
935/12	12 m	1/4" - black rubber - 600 bar	6,3 x 17,5	M 3/8"G	M 1/4"G	zinc plated steel
935/13	12 m	1/4" - black rubber - 600 bar	6,3 x 17,5	F 1/4"G	M 1/4"G	zinc plated steel
935/16	16 m	1/4" - black rubber - 600 bar	6,3 x 17,5	M 3/8"G	M 1/4"G	zinc plated steel
935/18	18 m	1/4" - black rubber - 600 bar	6,3 x 17,5	F 1/4"G	M 1/4"G	zinc plated steel
957/10	10 m	3/8" - black rubber - 600 bar	9,5 x 18	F 3/8"G	M 1/4"G	zinc plated steel
957/15	15 m	3/8" - black rubber - 600 bar	9,5 x 18	F 3/8"G	M 1/4"G	zinc plated steel
957/20	20 m	3/8" - black rubber - 600 bar	9,5 x 18	F 3/8"G	M 1/4"G	zinc plated steel
957/25	25 m	3/8" - black rubber - 600 bar	9,5 x 18	F 3/8"G	M 1/4"G	zinc plated steel
957/30	30 m	3/8" - black rubber - 600 bar	9,5 x 18	F 3/8"G	M 1/4"G	zinc plated steel



Special antistatic hoses (fuels, AdBlue)

Diesel and kerosene, fuel oil 10 bar

Article	Length	Characteristic - Pressure	Inside - \varnothing - Outside	Inlet	Outlet	Connections
968/20	20 m	1/2" - rubber NBR-EPDM antistatic - 10 bar	13 x 20	F 1/2"G	M 1/2"G	zinc plated steel
968/25	25 m	1/2" - rubber NBR-EPDM antistatic - 10 bar	13 x 20	F 1/2"G	M 1/2"G	zinc plated steel
978/12	12 m	3/4" - rubber NBR-EPDM antistatic - 10 bar	19 x 27	F 3/4"G	M 3/4"G	zinc plated steel
978/15	15 m	3/4" - rubber NBR-EPDM antistatic - 10 bar	19 x 27	F 3/4"G	M 3/4"G	zinc plated steel
978/20	20 m	3/4" - rubber NBR-EPDM antistatic - 10 bar	19 x 27	F 3/4"G	M 3/4"G	zinc plated steel
978/30	30 m	3/4" - rubber NBR-EPDM antistatic - 10 bar	19 x 27	F 3/4"G	M 3/4"G	zinc plated steel
978/35	35 m	3/4" - rubber NBR-EPDM antistatic - 10 bar	19 x 27	F 3/4"G	M 3/4"G	zinc plated steel
978/40	40 m	3/4" - rubber NBR-EPDM antistatic - 10 bar	19 x 27	F 3/4"G	M 3/4"G	zinc plated steel
978/50	50 m	3/4" - rubber NBR-EPDM antistatic - 10 bar	19 x 27	F 3/4"G	M 3/4"G	zinc plated steel
978/60	60 m	3/4" - rubber NBR-EPDM antistatic - 10 bar	19 x 27	F 3/4"G	M 3/4"G	zinc plated steel
988/8	8 m	1" - rubber NBR-EPDM antistatic - 10 bar	25 x 35	F 1"G	M 1"G	zinc plated steel
988/15	15 m	1" - rubber NBR-EPDM antistatic - 10 bar	25 x 35	F 1"G	M 1"G	zinc plated steel
988/20	20 m	1" - rubber NBR-EPDM antistatic - 10 bar	25 x 35	F 1"G	M 1"G	zinc plated steel
988/30	30 m	1" - rubber NBR-EPDM antistatic - 10 bar	25 x 35	F 1"G	M 1"G	zinc plated steel
988/40	40 m	1" - rubber NBR-EPDM antistatic - 10 bar	25 x 35	F 1"G	M 1"G	zinc plated steel
9103/15	15 m	1.1/4" - rubber NBR antistatic - 10 bar	32 x 44	M 1.1/4"G	M 1.1/4"G	zinc plated steel
9103/20	20 m	1.1/4" - rubber NBR antistatic - 10 bar	32 x 44	M 1.1/4"G	M 1.1/4"G	zinc plated steel
9103/25	25 m	1.1/4" - rubber NBR antistatic - 10 bar	32 x 44	M 1.1/4"G	M 1.1/4"G	zinc plated steel
9103/30	30 m	1.1/4" - rubber NBR antistatic - 10 bar	32 x 44	M 1.1/4"G	M 1.1/4"G	zinc plated steel
9113/10	10 m	1.1/2" - rubber NBR antistatic - 10 bar	38 x 50	M 1.1/2"G	M 1.1/2"G	zinc plated steel
9113/15	15 m	1.1/2" - rubber NBR antistatic - 10 bar	38 x 50	M 1.1/2"G	M 1.1/2"G	zinc plated steel
9113/20	20 m	1.1/2" - rubber NBR antistatic - 10 bar	38 x 50	M 1.1/2"G	M 1.1/2"G	zinc plated steel

AdBlue 10 bar

Article	Length	Characteristic - Pressure	Inside - \varnothing - Outside	Inlet	Outlet	Connections
892/10	10 m	5/8" - rubber EPDM antistatic - 10 bar	16 x 23	F 3/4"G	M 3/4"G	st. steel AISI 316
892/15	15 m	5/8" - rubber EPDM antistatic - 10 bar	16 x 23	F 3/4"G	M 3/4"G	st. steel AISI 316
892/20	20 m	5/8" - rubber EPDM antistatic - 10 bar	16 x 23	F 3/4"G	M 3/4"G	st. steel AISI 316
872/10	10 m	3/4" - rubber EPDM antistatic - 10 bar	19 x 27	F 3/4"G	M 3/4"G	st. steel AISI 316
872/15	15 m	3/4" - rubber EPDM antistatic - 10 bar	19 x 27	F 3/4"G	M 3/4"G	st. steel AISI 316

SPECIAL hoses EN 559



Special hoses EN 559 (welding, gas)

Oxygen - acetylene dual line hose 20 bar

Article	Length	Characteristic - Pressure	Inside - \emptyset - Outside	Inlet	Outlet	Connections
993/13	13 m	2 x 1/4" - SBR-EPDM - EN 559 - 20 bar	6,3 + 6,3x13	F 3/8"G	F 3/8"G	brass
993/17	17 m	2 x 1/4" - SBR-EPDM - EN 559 - 20 bar	6,3 + 6,3x13	F 3/8"G	F 3/8"G	brass
993/20	20 m	2 x 1/4" - SBR-EPDM - EN 559 - 20 bar	6,3 + 6,3x13	F 3/8"G	F 3/8"G	brass
993/25	25 m	2 x 1/4" - SBR-EPDM - EN 559 - 20 bar	6,3 + 6,3x13	F 3/8"G	F 3/8"G	brass
993/30	30 m	2 x 1/4" - SBR-EPDM - EN 559 - 20 bar	6,3 + 6,3x13	F 3/8"G	F 3/8"G	brass
993/35	35 m	2 x 1/4" - SBR-EPDM - EN 559 - 20 bar	6,3 + 6,3x13	F 3/8"G	F 3/8"G	brass
994/12	12 m	2 x 5/16" - SBR-EPDM - EN 559 - 20 bar	8 + 8x15	F 3/8"G	F 3/8"G	brass
994/15	15 m	2 x 5/16" - SBR-EPDM - EN 559 - 20 bar	8 + 8x15	F 3/8"G	F 3/8"G	brass
994/20	20 m	2 x 5/16" - SBR-EPDM - EN 559 - 20 bar	8 + 8x15	F 3/8"G	F 3/8"G	brass
994/25	25 m	2 x 5/16" - SBR-EPDM - EN 559 - 20 bar	8 + 8x15	F 3/8"G	F 3/8"G	brass
994/30	30 m	2 x 5/16" - SBR-EPDM - EN 559 - 20 bar	8 + 8x15	F 3/8"G	F 3/8"G	brass
994/35	35 m	2 x 5/16" - SBR-EPDM - EN 559 - 20 bar	8 + 8x15	F 3/8"G	F 3/8"G	brass
995/15	15 m	2 x 3/8" - SBR-EPDM - EN 559 - 20 bar	9 + 9x16	F 3/8"G	F 3/8"G	brass
995/20	20 m	2 x 3/8" - SBR-EPDM - EN 559 - 20 bar	9 + 9x16	F 3/8"G	F 3/8"G	brass
995/25	25 m	2 x 3/8" - SBR-EPDM - EN 559 - 20 bar	9 + 9x16	F 3/8"G	F 3/8"G	brass
995/27	27 m	2 x 3/8" - SBR-EPDM - EN 559 - 20 bar	9 + 9x16	F 3/8"G	F 3/8"G	brass

LPG, methane, natural gas 20 bar

Article	Length	Characteristic - Pressure	Inside - \emptyset - Outside	Inlet	Outlet	Connections
949/8	8 m	5/16" - NBR-PVC - EN 559 - 20 bar	8 x 15	F 3/8"G - Sx	F 3/8"G - Sx	brass
949/15	15 m	5/16" - NBR-PVC - EN 559 - 20 bar	8 x 15	F 3/8"G - Sx	F 3/8"G - Sx	brass
949/20	20 m	5/16" - NBR-PVC - EN 559 - 20 bar	8 x 15	F 3/8"G - Sx	F 3/8"G - Sx	brass
949/24	24 m	5/16" - NBR-PVC - EN 559 - 20 bar	8 x 15	F 3/8"G - Sx	F 3/8"G - Sx	brass
949/28	28 m	5/16" - NBR-PVC - EN 559 - 20 bar	8 x 15	F 3/8"G - Sx	F 3/8"G - Sx	brass
949/30	30 m	5/16" - NBR-PVC - EN 559 - 20 bar	8 x 15	F 3/8"G - Sx	F 3/8"G - Sx	brass
959/10	10 m	3/8" - NBR-PVC - EN 559 - 20 bar	10 x 17	F 3/8"G - Sx	F 3/8"G - Sx	brass
959/12	12 m	3/8" - NBR-PVC - EN 559 - 20 bar	10 x 17	F 3/8"G - Sx	F 3/8"G - Sx	brass
959/15	15 m	3/8" - NBR-PVC - EN 559 - 20 bar	10 x 17	F 3/8"G - Sx	F 3/8"G - Sx	brass
959/18	18 m	3/8" - NBR-PVC - EN 559 - 20 bar	10 x 17	F 3/8"G - Sx	F 3/8"G - Sx	brass
959/22	22 m	3/8" - NBR-PVC - EN 559 - 20 bar	10 x 17	F 3/8"G - Sx	F 3/8"G - Sx	brass
959/27	27 m	3/8" - NBR-PVC - EN 559 - 20 bar	10 x 17	F 3/8"G - Sx	F 3/8"G - Sx	brass
959/30	30 m	3/8" - NBR-PVC - EN 559 - 20 bar	10 x 17	F 3/8"G - Sx	F 3/8"G - Sx	brass